

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
Please do not report the images to the
Image Problem Mailbox.

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: A61B	A2	(11) International Publication Number: WO 00/57766
		(43) International Publication Date: 05 October 2000 (05.10.2000)

(21) International Application Number:	PCT/IB00/00236
(22) International Filing Date:	09 March 2000 (09.03.2000)
(30) Priority Data:	128904 09 March 1999 (09.03.1999) IL
(60) Parent Application or Grant	INTA MEDICS, LTD. [/]; (). MICHAELI, David [/]; (). MICHAELI, David [/]; ().

Published

- (54) Title: ULTRASOUND PULSATILITY IMAGING
(54) Titre: IMAGERIE PAR ULTRASONS POUR L'OBSERVATION DE L'ACTIVITE PULSATOIRE

(57) Abstract

A method for observing three-dimensional pulsatile activity in a preselected volume of tissue in a subject is provided, wherein the volume of tissue has a length, width, and depth. The method includes the steps of: placing an array of ultrasound probes in association with the surface of the subject; selecting a generally linear subset of the array arranged in association with a selected slice of the preselected volume of tissue, said linear subset forming a subarray of said array of probes, wherein the selected slice has a length and a width, and at least a predetermined depth; activating and focusing at least a selected contiguous portion of the selected subset of the array of probes, the selected contiguous portion of the selected subset of the array having a predetermined curvature, so that each probe is operative: to emit ultrasound waves in a preselected frequency waveband and at a preselected range of output intensities, to receive reflected ultrasound energy from the tissue in the preselected frequency waveband, and to convert the received reflected ultrasound energy into output signals corresponding thereto. The method further includes the steps of focusing the ultrasound energy of the probes constituting the selected contiguous portion of the subarray of probes in a selected portion of the selected slice of tissue along a selected line, wherein the selected line is contained within the selected slice and intersects the linear subset of probes; receiving, via the probes constituting the selected contiguous portion of the subarray of probes, the reflected ultrasound energy from the tissue and converting it into output signals corresponding to the reflected ultrasound energy; processing the output signals from the probes constituting the selected contiguous portion of the subarray of probes so as to determine pulsatile activity in the selected portion of the selected tissue slice; providing output data corresponding to the pulsatile activity in the selected portion of the selected tissue slice; varying the focus of the ultrasound energy along the line within the volume slice and repeating said step of receiving and converting and said steps of processing and of providing for each of a sequence of selected portions of the selected tissue slice along the full extent of the selected line there within; selecting a sequence of contiguous portions of the selected subset of the array and repeating for each of the selected sequence said step of activating and focusing, said step of receiving and converting, and said step of processing, further repeating for each selected portion of tissue said step of providing output data, and further repeating for each of the selected sequence said step of varying the focus; thereby to select additional lines within the selected slice and to determine pulsatile activity and to provide output data corresponding thereto along a multiplicity of selected lines along the full extent of the selected slice; selecting a sequence of subsets of the array of ultrasound probes and repeating thereon said step of selecting a sequence of contiguous portions of the selected subset of the array, thereby to select additional slices within the preselected volume, so as to determine pulsatile activity and to provide output data corresponding thereto along a multiplicity of slices of tissue within the preselected volume along the full extent thereof; and performing tomographic analysis of the output data corresponding to pulsatile activity in the plurality of selected portions of tissue, so as to obtain a three dimensional image of pulsatile activity in the preselected volume of tissue.

(57) Abrégé

L'invention concerne un procédé permettant d'observer l'activité pulsatoire tridimensionnelle dans un volume prédéterminé de tissu chez un sujet, ce volume de tissu ayant une certaine longueur, une certaine largeur et une certaine profondeur. Le procédé comprend les étapes suivantes: placer un réseau de sondes à ultrasons sur la surface du sujet; sélectionner un sous-ensemble généralement linéaire du réseau en association avec une tranche sélectionnée du volume de tissu prédéterminé, ledit sous-ensemble linéaire formant un sous-réseau dudit réseau de sondes, ladite tranche sélectionnée ayant une certaine longueur et une certaine largeur, et au moins une profondeur prédéterminée; activer et focaliser au moins une portion contiguë sélectionnée du sous-ensemble sélectionné du réseau de sondes, ladite portion ayant une courbure prédéterminée de sorte que chaque sonde soit opérationnelle dans le but d'émettre des ondes ultrasoniques dans une bande d'ondes de fréquence prédéterminée ayant des intensités de sortie dans une plage prédéterminée, de recevoir l'énergie ultrasonique réfléchie par les tissus dans une bande d'ondes de fréquence prédéterminée, et de convertir l'énergie ultrasonique réfléchie reçue en signaux de sortie. Le procédé comprend également les étapes de focalisation de l'énergie à ultrasons des sondes qui constituent la partie contiguë sélectionnée du sous-ensemble de sondes dans une partie sélectionnée de la tranche sélectionnée de tissu le long d'une ligne sélectionnée qui est contenue dans la tranche sélectionnée et intersecte le sous-ensemble linéaire de sondes; de réception, par l'intermédiaire des sondes formant la partie contiguë sélectionnée du sous-ensemble de sondes, de l'énergie à ultrasons réfléchie par les tissus


et de conversion de cette énergie en signaux de sortie correspondant à l'énergie ultrasonique réfléchie; de traitement des signaux de sortie provenant des sondes formant la partie contiguë sélectionnée du sous-ensemble de sondes afin de déterminer l'activité pulsatoire dans la partie sélectionnée de la tranche de tissu sélectionnée; de production de données de sortie correspondant à l'activité pulsatoire dans la partie sélectionnée de la tranche de tissu sélectionnée; de variation du point de focalisation de l'énergie à ultrasons le long de la ligne dans la tranche sélectionnée du volume de tissu et de répétition de ladite étape de réception et de conversion ainsi que de traitement et de production de données pour chaque portion d'une série de portions sélectionnées de la tranche de tissu sélectionnée sur toute la longueur de la ligne sélectionnée; de sélection d'une série de portions contiguës du sous-ensemble sélectionné du réseau de sondes et de répétition pour chacune des séries sélectionnées des étapes d'activation et de focalisation, des étapes de réception et de conversion, et de ladite étape de traitement, et de répétition pour chaque portion sélectionnée de tissu de l'étape de production des données de sortie, et de répétition pour chacune des séries sélectionnées de ladite étape de variation du point de focalisation; sélection des lignes additionnelles dans la tranche sélectionnée et détermination de l'activité pulsatoire et production des données de sortie correspondantes le long d'une multitude de lignes sélectionnées sur toute la longueur de la tranche sélectionnée; sélection d'une série de sous-ensembles du réseau de sondes ultrasoniques et répétition de ladite étape de sélection d'une série de portions contiguës du sous-ensemble sélectionné du réseau afin de sélectionner des tranches additionnelles dans le volume présélectionné de tissu pour déterminer l'activité pulsatoire et produire des données de sortie correspondantes le long d'une multitude de tranches de tissu dans le volume présélectionné, et effectuer l'analyse tomographique des données de sortie correspondantes à l'activité pulsatoire dans la pluralité de portions sélectionnées de tissu afin d'obtenir une image tridimensionnelle de l'activité pulsatoire dans le volume présélectionné de tissu.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B	A2	(11) International Publication Number: WO 00/57766 (43) International Publication Date: 5 October 2000 (05.10.00)
(21) International Application Number: PCT/IB00/00236 (22) International Filing Date: 9 March 2000 (09.03.00) (30) Priority Data: 128904 9 March 1999 (09.03.99) IL (71) Applicant (for all designated States except US): INTA MEDICS, LTD. (IL/IL); South Industrial Zone, Ashkelon, P.O. Box 7284, 78172 Ashkelon (IL). (72) Inventor; and (75) Inventor/Applicant (for US only): MICHAELI, David (IL/IL); Mitheshivan 7/6, 70720 Ashkelon (IL).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published Without international search report and to be republished upon receipt of that report.	
(54) Title: ULTRASOUND PULSATILITY IMAGING		
(57) Abstract <p>A method for observing three-dimensional pulsatile activity in a preselected volume of tissue in a subject is provided, wherein the volume of tissue has a length, width, and depth. The method includes the steps of: placing an array of ultrasound probes in association with the surface of the subject; selecting a generally linear subset of the array arranged in association with a selected slice of the preselected volume of tissue, said linear subset forming a subarray of said array of probes, wherein the selected slice has a length and a width, and at least a predetermined depth; activating and focusing at least a selected contiguous portion of the selected subset of the array of probes, the selected contiguous portion of the selected subset of the array having a predetermined curvature, so that each probe is operative: to emit ultrasound waves in a preselected frequency waveband and at a preselected range of output intensities, to receive reflected ultrasound energy from the tissue in the preselected frequency waveband, and to convert the received reflected ultrasound energy into output signals corresponding thereto. The method further includes the steps of focusing the ultrasound energy of the probes constituting the selected contiguous portion of the subarray of probes in a selected portion of the selected slice of tissue along a selected line, wherein the selected line is contained within the selected slice and intersects the linear subset of probes; receiving, via the probes constituting the selected contiguous portion of the subarray of probes, the reflected ultrasound energy from the tissue and converting it into output signals corresponding to the reflected ultrasound energy; processing the output signals from the probes constituting the selected contiguous portion of the subarray of probes so as to determine pulsatile activity in the selected portion of the selected tissue slice; providing output data corresponding to the pulsatile activity in the selected portion of the selected tissue slice; varying the focus of the ultrasound energy along the line within the volume slice and repeating said step of receiving and converting and said steps of processing and of providing for each of a sequence of selected portions of the selected tissue slice along the full extent of the selected line there within; selecting a sequence of contiguous portions of the selected subset of the array and repeating for each of the selected sequence said step of activating and focusing, said step of receiving and converting, and said step of processing, further repeating for each selected portion of tissue said step of providing output data, and further repeating for each of the selected sequence said step of varying the focus; thereby to select additional lines within the selected slice and to determine pulsatile activity and to provide output data corresponding thereto along a multiplicity of selected lines along the full extent of the selected slice; selecting a sequence of subsets of the array of ultrasound probes and repeating thereon said step of selecting a sequence of contiguous portions of the selected subset of the array, thereby to select additional slices within the preselected volume, so as to determine pulsatile activity and to provide output data corresponding thereto along a multiplicity of slices of tissue within the preselected volume along the full extent thereof; and performing tomographic analysis of the output data corresponding to pulsatile activity in the plurality of selected portions of tissue, so as to obtain a three dimensional image of pulsatile activity in the preselected volume of tissue.</p>		



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
DJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Description

5

10

15

20

25

30

35

40

45

50

55

ULTRASOUND PULSATILITY IMAGING**FIELD OF THE INVENTION**

The present invention relates generally to the use of ultrasound to observe pulsatile activity in living tissue.

BACKGROUND OF THE INVENTION

Ultrasound imaging provides a non-invasive means to view internal portions of a patient's body, and so has proven a useful medical diagnostic tool. Ultrasound waves, typically of a frequency in the range of 2 to 20 MHz, are emitted into the body of the patient and reflected ultrasound waves from the body tissues are received and converted into signals which are processed to produce an image. These images, while useful, have been limited in that they were two-dimensional and of low resolution. Recently, higher resolution and three-dimensional ultrasound images have become available, but without real-time imaging, as they require many measurements and significant data processing time to produce the images. Even advanced existing ultrasound imaging systems do not allow observation of pulsatile behavior, which can be a valuable diagnostic tool, in the tissue being examined.

A further limitation of existing ultrasound imaging systems is that the ultrasound waves they use undergo significant attenuation when passing through bone, which limits their usefulness for observing certain regions of the body, especially the brain.

US patent 5,840,018, granted to the present inventor, discloses a method to perform real-time observations on blood vessels in the brain; the contents of this patent are incorporated herein by reference. It includes means and method for processing and analyzing time varying signals associated with pulsatile activity in blood vessels, especially by employing gating circuitry.

5 US Patent 4,549,533 discloses apparatus and method to generate and direct ultrasound energy over a predetermined region of the body, but the application disclosed therein is only for directing the ultrasound energy to the target region, without detecting reflected ultrasound energy to observe the target region.

10 US Patent 5,540,230 discloses apparatus and method employing ultrasound to determine the velocity of fluid flowing through a lumen. US Patent 5,394,750 discloses an ultrasound transceiver which includes filtering on received signals to reduce noise in detected signals and which may be employed to determine the velocity profile of blood flow in tissue. Both inventions disclosed therein only allow observation of a single point with no provision for multiple observations in real time.

15 US Patent 5,787,889 discloses a method and an ultrasound system for three-dimensional ultrasound imaging in real time, but is restricted to a physical image of the tissue being scanned, without observing pulsatility details. It is further limited by operator movement of the ultrasound transducer/receiver over the surface of the patient; indeed, the real-time imaging disclosed therein corresponds to tracking this manual probe movement. Further, ultrasound waves in the frequency range cited therein are subject to significant attenuation when passing through bone, resulting in the above mentioned limitation of applicability.

35 SUMMARY OF THE INVENTION

40 An aim of the present invention is to provide a method to image a volume of tissue in a subject with ultrasound waves that overcomes the limitations of the prior art by providing a dynamic three-dimensional representation and at a high resolution of pulsatile activity in the selected volume of tissue.

45 There is thus provided, in accordance with a preferred embodiment of the invention, a method for observing three-dimensional pulsatile activity in a preselected volume of tissue in a subject that includes the following steps:

- 5 • placing an array of ultrasound probes in association with the surface of the subject, thereby selecting a discrete volume of tissue in the subject;
- 10 • selecting a generally linear subset of the array, thereby defining a thin slice of the selected volume of tissue;
- 15 • activating and focusing a selected contiguous portion, having a predetermined curvature, of the selected subset of the array of probes, so that each probe is operative:

20 to emit ultrasound waves in a preselected frequency waveband and at a preselected range of output intensities, typically with a bandwidth of substantially 0.4 MHz in the frequency range 0.4-40.0 MHz and an output intensity in the
25 range 100-300 mW/cm², but especially in a waveband selected so as not to be substantially attenuated by bone,

30 to receive reflected ultrasound energy from the tissue in the preselected frequency waveband, and

35 to convert the received reflected ultrasound energy into output signals corresponding thereto;

40 and so that the focusing serves to select a portion of tissue along a line contained within the selected tissue slice which further intersects the linear subset of probes, the volume of the selected portion of the tissue slice defines the pixel size for the image that is desired to be produced, which is in the range 0.1 to 1.0 mm³;

45 receiving, via the probes constituting the selected contiguous portion of the subarray of probes, the reflected ultrasound energy from the tissue and converting it into output
50

5 signals corresponding to the reflected ultrasound energy;

10 • processing these output signals from the probes so as to determine pulsatile activity in the selected portion of the selected tissue slice;

15 • providing output data corresponding to the pulsatile activity in the selected portion of the selected tissue slice;

20 • varying the focus of the ultrasound energy along the line within the volume slice and repeating above steps thereby scanning the selected line within the selected tissue slice and providing output data corresponding to the pulsatile activity in successive portions of tissue along the line;

25 • selecting a sequence of contiguous portions of the selected subset of the array and repeating above steps thereby selecting a sequence of lines within the selected tissue slice, thereby scanning the selected tissue slice and providing output data corresponding to the pulsatile activity in successive portions of tissue along the lines within the slice;

30 • selecting a sequence of subsets of the array of ultrasound probes and repeating above steps thereby selecting a sequence of slices within the selected tissue volume, thereby scanning the selected volume and providing output data corresponding to the pulsatile activity in successive slices of tissue within the volume; and

35 • performing tomographic analysis of the plurality of output data, thereby obtaining a three-dimensional image of the pulsatile activity in the selected volume of tissue.

5 Further in accordance with a preferred embodiment of the present invention, the sequence of slices within the selected tissue volume is a sequence of substantially parallel first slices, and the method further includes the following steps:

10 selecting additional linear subsets of the array of ultrasonic probes arranged in association with a second tissue slice having a non-parallel alignment with respect to the first tissue slices;

15 repeating the step of selecting a sequence of subsets of the array arranged in association with additional tissue slices parallel to the second tissue slice; and

20 performing tomographic analysis of the plurality of output data, thereby obtaining a directional three-dimensional image of the pulsatile activity in the selected volume of tissue.

25 Before performing the tomographic analysis, additional linear subsets in association with subsequent tissue slices having non-parallel alignment with respect to both first and second tissue slices may further be selected. This, together with repetition of the step of selecting a sequence of subsets, provides more directional information to the three dimensional image of the pulsatile activity in the selected volume of tissue so obtained.

35 In accordance with the alternative preferred embodiments of the present invention, the step of activating and focusing may include changing the curvature of the selected contiguous portion of the linear subarray of ultrasound probes or adjusting the timing of the activation of the selected contiguous portion of the subarray of ultrasound probes, so as to focus the ultrasound energy variably within the selected tissue slice and to observe pulsatile activity therein. The frequency waveband of the ultrasound waves may also be varied.

45 Further in accordance with a preferred embodiment of the invention, the step of processing the output signals includes the substeps of:

5 converting the output signals into a summed output signal associated with the selected portion of the selected tissue slice;

10 measuring variation in the summed output signal as a function of time; and

observing selected features of pulsatile activity in the time variation of the summed output signal associated with the selected portion of the selected tissue slice, typically by
15 applying gating circuitry to the time variation.

Additionally in accordance with a preferred embodiment of the invention, the substep of
20 observing selected features of pulsatile activity includes the substeps of:

performing spectral analysis of the summed output signal associated with the selected portion of the selected tissue slice to produce a frequency spectrum associated therewith;
25

selecting a reference pulsatile signal associated with the heart rate of the subject, such as an electrocardiogram signal;

30 performing spectral analysis of the reference pulsatile signal associated with the heart rate of the subject to produce a frequency spectrum associated therewith; and

35 comparing the frequency spectrum of the summed output signal associated with the selected portion of the selected tissue slice with the frequency spectrum of the reference pulsatile signal.
40

5 **BRIEF DESCRIPTION OF THE DRAWINGS**

10 The present invention will be more fully understood and appreciated from the following detailed description, taken in conjunction with the drawings, in which:

15 Figures 1A and 1B are two views of the head of a subject with an array of ultrasound probes in association therewith in accordance with a method which is a preferred embodiment of the present invention;

20 Figure 2 is a view of a tissue slice of the subject and a subset of the array of ultrasound probes of Figure 1;

25 Figure 3 is a schematic view of the step of varying the focus of a group of ultrasound probes in accordance with a preferred embodiment of the present invention;

30 Figure 4 is a graph of the time dependent signal observed in a portion of pulsing tissue;

35 Figure 5 is a schematic view of multiply-oriented tissue slices in the same tissue sample of the subject of Figure 1;

40 Figure 6 is a flow chart of the method in accordance with a preferred embodiment of the present invention.

45 **DETAILED DESCRIPTION OF THE INVENTION**

50 Referring now to Figures 1A through 5, there are shown an example of a system and details of its operation for observing three-dimensional pulsatile activity in a volume of tissue in a subject in accordance with a preferred embodiment of the present invention.

5 Referring now to Figures 1A and 1B, there are shown, by way of example, two views,
overhead and transverse, of the head 11 of a subject with an array, referred to generally as 10, of
ultrasound probes 15 arranged in association with the surface thereof, in accordance with a
10 method which is a preferred embodiment of the present invention. Probes 15 are operative to
emit ultrasound waves via the surface of the subject into a discrete volume of tissue in the
subject, in the present example, the brain of the subject, and to detect reflected ultrasound energy
therefrom. A thin slice of the tissue volume is defined by a selected generally linear subset of
15 array 10 of probes 15 bordering thereon, indicated by box 17 in the drawings. In the present
embodiment, probes 15 may be 2 mm x 2 mm in size, and the slice may have a depth or thickness
as small as 0.1 mm.

20 Referring now to Figure 2, there is shown tissue slice 21 surrounded by a subset, referred
to generally as 20, of ultrasound probes 25. In subset 20, a contiguous group 27 of at least three
probes 25, encircled in the drawing, representing a portion of subset 20, is activated to emit, into
25 tissue slice 21, ultrasound waves in the frequency range 0.4-40.0 MHz with a typical bandwidth
of approximately 0.4 MHz and an output intensity in the range 100-300 mW/cm². Probes 25 are
further operative to detect reflected ultrasound energy from the tissue in slice 21. If, as in the
30 present example, the tissue being observed is brain tissue, lower frequencies in the given range
will, for a large portion of the population, reach the brain tissue with minimal attenuation passing
through the bone of the skull.

35 As will be understood by persons skilled in the art, the curvature of the line connecting
group 27 of probes produces a focusing effect with the ultrasound waves emitted thereby,
wherein the ultrasound waves interfere constructively at a discrete location in the tissue being
40 observed. It is worth noting that this constructive interference causes reflected ultrasound energy
from the discrete location 29 in the tissue being observed to be of a magnitude significantly
greater than that reflected from other locations in the tissue, thereby allowing reflected ultrasound
energy from that location to be readily distinguished from that reflected from other locations,
45 which may be referred to as "background" ultrasound energy. It is in this sense that it is
meaningful to refer to observing the discrete location or focusing thereon. This effective focal
point corresponds to a small portion 29 of the tissue, which falls on a line 28 in tissue slice 21

5 which intersects group 27 of probes, thereby defining the pixel volume for the observations, which, in accordance with a preferred embodiment of the present invention, can be as small as 0.1 mm³.

10 Referring briefly to Figure 3, there is shown the effect of slightly changing the positions of the probes constituting a group, referred to generally as 30, of probes 35 relative to one another, thereby varying the curvature of the line connecting them. As is shown in the drawing, 15 as the curvature increases, the focus of the ultrasound waves emitted by group 30 of probes 35 becomes shorter, moving closer to the line of probes. Probes 35 may be moved to effect the change in curvature, for example, by individual piezoelectric actuators in association therewith.

20 As will be further understood by persons skilled in the art, change of focus can also be effected by controlling the timing of the ultrasound emission from the individual probes 35 of group 30 to produce the same constructive interference as that produced by curvature of group 30 25 of probes.

30 Returning now to Figure 2, it can be seen that by suitably varying the focus of group 27 of probes, successive portions or pixels 29 of tissue can be selected for observation along line 28 covering its full extent within tissue slice 21. The drawing also shows a second group 27A of probes 25, which can be selectively activated in similar fashion to group 27 to allow observation 35 along a second line 28A within tissue slice 21. By selecting successive groups of probes, a sequence of lines of pixels can be selected for observation to allow observation of tissue slice 21, pixel by pixel and line by line providing complete coverage thereof.

40 Referring again briefly to Figure 1A, a series of generally parallel slices of the tissue volume can be defined selecting successive generally linear subsets of array 10 of probes 15 to allow observation of the entire tissue volume, pixel by pixel, line by line, and slice by slice providing 45 complete coverage thereof.

50 To summarize: by selection of successive generally linear subsets of probes from array 10, successive contiguous groups of probes 15 therewithin, and successive focal points

5 thereof, a series of pixels within the tissue may be observed which covers the entire volume of the tissue, at a resolution depending on the pixel size.

10 Referring now to Figure 4, there is shown a graph of the reflected ultrasound energy detected from a selected pixel in tissue exhibiting pulsatile activity as a function of time. The graph exhibits a periodic pulsing with a characteristic waveform with a number of identifiable segments and features, labeled t_1 , t_3 , t_4 , and E_B , for example, in the drawing. As will be
15 understood by persons skilled in the art, these can be used to identify specific structures within the tissue; for example, in the case of brain tissue, blood vessels and chambers known as ventricles may be identified by their observed pulsatile activity. In accordance with a method
20 which is a preferred embodiment of the present invention, by applying gating circuitry to the time-dependent signal detected from the reflected ultrasound energy, a particular feature of the waveform or a parameter derived therefrom, such as its slope may be observed for all or a
25 selected portion of pixels in the tissue.

In accordance with a method which is a further preferred embodiment of the present invention, spectral analysis may be performed on the time-dependent signal detected from the
30 reflected ultrasound energy to produce a frequency spectrum associated therewith. By comparing the frequency spectrum associated with reflected ultrasound energy from selected tissue in the subject and the frequency spectrum produced by spectral analysis of any reference pulsatile signal associated with the heart rate of the subject, such as an electrocardiogram signal or any arterial
35 pulse, useful diagnostic information may be obtained. In the present example, frequency shifts or offsets from the heart rate of the subject in the brain of the subject, can indicate migraine activity, edemas, or aneurysms.

40 By collecting and storing these sequences of observations in a suitably programmed data processing apparatus, the known method of tomographic analysis may be performed on the observations to produce an image of the three dimensional variation of the selected parameter
45 in the tissue being observed.

5 As will be understood by persons skilled in the art, some observations of pulsatile activity will vary with the orientation or direction of the observations. In some cases, change of orientation can optimize observation for more usable information, by increasing contrast in the resulting image; in other cases, what is observed has a three-dimensional or vectorial nature. 10 Referring now to Figure 5, there is shown a portion of tissue to be observed by the method of the present invention with a number of tissue slices with varying, non-parallel, orientations indicated therein. Pulsatile activity in the tissue in the varying directions may be observed by selecting 15 suitable first subsets of an array of probes in association with the tissue. By further selecting a sequence of subsets parallel to the first sets, the entire volume of tissue may be observed. For example, observations may be made along three perpendicular axes to obtain full vectorial information about pulsatile activity in the tissue. This data may also be analyzed tomographically 20 to produce a full, directional three-dimensional image of the pulsatile activity in the tissue.

25 Referring now to Figure 6, there is shown a flowchart for the method of the present invention. In the following discussion, steps of the method are referred to by letters in Figure 6, and parts of a system to implement the method are referred to by numbers in Figures 1A through 5. 30

In accordance with a preferred embodiment of the present invention, a method for observing three-dimensional pulsatile activity in a volume of tissue in a subject of the present invention follows: 35

- 40 A. An array 10 of ultrasound probes 15 is placed in association with the surface of the subject, which serves to select a discrete volume of tissue in the subject; in the present example, the brain of the subject.
- 45 B. A generally linear subset of the array, indicated by box 17 in Figures 1A and 1B, is selected. This defines a thin slice of the selected volume of tissue, which, in the present embodiment, has a depth or thickness of approximately 1.0 mm.

5
C. A group of probes which is a selected contiguous portion of the selected subset of the
array of probes, encircled and indicated by 27 in Figure 2, is activated and focused. The
10 activated probes are each operative:

15 to emit ultrasound waves in a preselected frequency waveband and at a
preselected range of output intensities;

20 to receive reflected ultrasound energy from the tissue in the preselected frequency
waveband, and

25 to convert the received reflected ultrasound energy into an output signal.

30 In the present embodiment, the frequency waveband of the ultrasound waves emitted and
received by the ultrasound probes has a bandwidth of substantially 0.4 MHz in the
frequency range 0.4-40.0 MHz and the ultrasound waves are emitted with an output
intensity in the range 100-300 mW/cm². Further, in particular for the present example
wherein the selected tissue is brain tissue which is surrounded by the skull, the frequency
35 waveband of the ultrasound waves emitted and received by the ultrasound probes is
selected so as not to be substantially attenuated by bone tissue, which frequency
waveband, it should be noted, may vary depending on the subject.

40 It should further be noted that the selected contiguous portion of the selected subset of
the array of probes has a predetermined curvature which, as will be understood by those
familiar with the art and as discussed above, will result in the ultrasound energy of the
45 probes being focused in a selected portion 29 of the selected slice of tissue along a
selected line 28 that is contained within the selected slice 21 and that intersects the linear
subset of probes 20. The volume of the selected portion of the selected slice of tissue

5 defines the pixel size for the image that is desired to be produced by the present method,
which, in the present embodiment, is in the range 0.1 to 1.0 mm³.

10 D. Reflected ultrasound energy from the tissue is received by the probes and converted into
output signals corresponding thereto.

15 E. The output signals from the probes are processed to determine pulsatile activity in the
selected portion of the selected tissue slice. In accordance with a preferred embodiment
of the present invention, this may include:

20 converting the output signals into a summed output signal associated with the
selected portion of the selected tissue slice;

25 measuring variation in the summed output signal as a function of time; and

30 observing selected features of pulsatile activity in the time variation of the
summed output signal associated with the selected portion of the selected tissue
slice, which may be accomplished by applying gating circuitry to the time
variation of the summed output signal associated with the selected portion of the
selected tissue slice. In accordance with a further preferred embodiment of the
35 present invention, this may include:

40 performing spectral analysis of the summed output signal associated with
the selected portion of the selected tissue slice to produce a frequency
spectrum associated therewith;

45 selecting a reference pulsatile signal associated with the heart rate of the
subject, which may be an electrocardiogram signal or any arterial pulse;

5 performing spectral analysis of the reference pulsatile signal associated with the heart rate of the subject to produce a frequency spectrum associated therewith; and

10 comparing the frequency spectrum of the summed output signal associated with the selected portion of the selected tissue slice with the frequency spectrum of the reference pulsatile signal associated with the heart rate of the subject.

15 F. Output data corresponding to the pulsatile activity in the selected portion of the selected tissue slice is then provided and may be stored for later processing.

20 G. The focus of the ultrasound energy is varied along the selected line within the volume slice, and wherein the above steps:

25 (D.) reflected ultrasound energy from the tissue is received by the probes and converted into output signals corresponding thereto;

30 (E.) output signals from the probes are processed to determine pulsatile activity in the selected portion of the selected tissue slice; and

35 (F.) output data corresponding to the pulsatile activity in the selected portion of the selected tissue slice is provided,

40 are repeated for each of a sequence of pixels or selected portions of the selected volume slice along the full extent of the selected line within the volume slice. This scans the line completely, pixel by pixel, for pulsatile activity.

45 In a preferred embodiment of the present invention, the focus may be changed by changing the curvature of the selected contiguous portion of the linear subarray of

5 ultrasound probes, as shown in Figure 3, which may be effected, for example, by
piezoelectric actuators in association with the individual probes. In an alternative
embodiment of the present invention, the focus may be changed by adjusting the timing
10 of the activation of at least a selected contiguous portion of the subarray of ultrasound
probes. It is also possible to change the focus of the probes by varying the frequency
waveband of the ultrasound waves they emit.

15 H. To scan the selected slice of tissue line by line, a sequence of contiguous portions of the
selected subset of the array of probes is selected. For each member of the sequence, the
above step (C.) wherein the group of probes which is the selected contiguous portion of
20 the array of probes is activated and focused, the above steps (D.), (E.), and (F.) wherein
output data corresponding to pulsatile activity in the selected portion 29 of the selected
tissue slice 21 is provided, and the above step (G.) wherein the focus of the ultrasound
energy is varied along the selected line within the volume slice are repeated. This
25 produces output data corresponding to the pulsatile activity in the entire tissue slice.

30 I. To scan the entire selected volume of tissue slice by slice, a sequence of subsets of the
array of ultrasonic probes is selected. For each member of the sequence, the above
step (G) wherein a sequence of contiguous portions of the selected subset of the array of
35 probes is selected is repeated. This produces output data corresponding to the pulsatile
activity in the entire selected volume of tissue.

40 J. Finally, tomographic analysis of the entire plurality of output data is performed, so as to
obtain a three dimensional image of pulsatile activity in the selected volume of tissue.

45 Further in accordance with a preferred embodiment of the present invention, the method
may include an additional step, prior to the step (J.) wherein tomographic analysis is performed,
wherein the selected volume of tissue is again scanned slice by slice, as in step (I) above, with
this subsequent set of slices having a different, non-parallel, orientation with respect to the first
50 set of slices. This may be accomplished by a suitable choice of a sequence of subsets of the array

5 of ultrasonic probes. This may be repeated, for example, along three perpendicular axes to provide a directional or vectorial image of pulsatile activity in the selected tissue.

10 It will be appreciated by persons skilled in the art, that the scope of the present invention is not limited by what has been specifically shown and described hereinabove, merely by way of example. Rather, the scope of the present invention is defined solely by the claims, which
15 follow.

Claims

5

10

15

20

25

30

35

40

45

50

55

THIS PAGE BLANK (USPTO)

CLAIMS

1. A method for observing three-dimensional pulsatile activity in a preselected volume of tissue in a subject, the volume of tissue having a length, width, and depth, said method including the steps of:

- placing an array of ultrasound probes in association with the surface of the subject;
- selecting a generally linear subset of the array arranged in association with a selected slice of the preselected volume of tissue, said linear subset forming a subarray of said array of probes, wherein the selected slice has a length and a width, and at least a predetermined depth;
- activating and focusing at least a selected contiguous portion of the selected subset of the array of probes, the selected contiguous portion of the selected subset of the array having a predetermined curvature, so that each probe is operative:

to emit ultrasound waves in a preselected frequency waveband and at a preselected range of output intensities,

to receive reflected ultrasound energy from the tissue in the preselected frequency waveband, and

to convert the received reflected ultrasound energy into output signals corresponding thereto;

and including focusing the ultrasound energy of the probes constituting the selected contiguous portion of the subarray of probes in a selected portion of the selected slice of tissue along a selected line, wherein the selected line is contained within the selected slice and intersects the linear subset of probes;

- 5 • receiving, via the probes constituting the selected contiguous portion of the subarray of
 probes, the reflected ultrasound energy from the tissue and converting it into output
 signals corresponding to the reflected ultrasound energy;
- 10
- processing the output signals from the probes constituting the selected contiguous portion
 of the subarray of probes so as to determine pulsatile activity in the selected portion of
15 the selected tissue slice;
- providing output data corresponding to the pulsatile activity in the selected portion of the
20 selected tissue slice;
- varying the focus of the ultrasound energy along the line within the volume slice and
 repeating said step of receiving and converting and said steps of processing and of
25 providing for each of a sequence of selected portions of the selected tissue slice along the
 full extent of the selected line therewithin;
- 30 • selecting a sequence of contiguous portions of the selected subset of the array and
 repeating for each of the selected sequence said step of activating and focusing,
 said step of receiving and converting, and said step of processing,
- 35 further repeating for each selected portion of tissue said step of providing output
 data, and
 further repeating for each of the selected sequence said step of varying the focus;
40 thereby to select additional lines within the selected slice and to determine
 pulsatile activity and to provide output data corresponding thereto along a
 multiplicity of selected lines along the full extent of the selected slice;
- 45
- selecting a sequence of subsets of the array of ultrasound probes and repeating thereon
 said step of selecting a sequence of contiguous portions of the selected subset of the
50

5 array, thereby to select additional slices within the preselected volume, so as to determine
pulsatile activity and to provide output data corresponding thereto along a multiplicity
of slices of tissue within the preselected volume along the full extent thereof; and

- 10
- performing tomographic analysis of the output data corresponding to pulsatile activity in
the plurality of selected portions of tissue, so as to obtain a three dimensional image of
15 pulsatile activity in the preselected volume of tissue.

- 20 2. A method according to claim 1 wherein the multiplicity of slices is a multiplicity of
substantially parallel first slices, and said method further includes the steps of:

25 selecting additional linear subsets of the array of ultrasonic probes arranged in association
with a second tissue slice having a non-parallel alignment with respect to the first tissue
slices;

30 repeating said step of selecting a sequence of subsets of the array arranged in association
with additional tissue slices parallel to the second tissue slice; and

35 performing tomographic analysis of the output data corresponding to pulsatile activity in
the plurality of selected portions of tissue, so as to obtain a directional three dimensional
image of pulsatile activity in the preselected volume of tissue.

- 40 3. A method according to claim 2 wherein said method further includes the steps, prior to
said step of performing tomographic analysis, of:

45 selecting further linear subsets of the array of ultrasonic probes arranged in association
with subsequent tissue slices having a non-parallel alignment with respect to both first
and second tissue slices; and

5 repeating said step of selecting a sequence of subsets of the array arranged in association
with additional tissue slices parallel to the second tissue slice.

- 10 4. A method according to claim 1 wherein said step of processing the output signals
includes the subsets of:

15 converting the output signals into a summed output signal associated with the selected
portion of the selected tissue slice;

measuring variation in the summed output signal as a function of time; and

20 observing selected features of pulsatile activity in the time variation of the summed
output signal associated with the selected portion of the selected tissue slice.

- 25 5. A method according to claim 1 wherein said step of activating and focusing includes the
substep of changing the curvature of the selected contiguous portion of the linear
subarray of ultrasound probes, so as to focus the ultrasound energy variably within the
selected tissue slice and to observe pulsatile activity therein.

- 30 6. A method according to claim 1 wherein said step of activating and focusing includes the
substep of adjusting the timing of the activation of at least a selected contiguous portion
35 of the subarray of ultrasound probes, so as to focus the ultrasound energy variably within
the selected tissue slice and to observe pulsatile activity therein.

- 40 7. A method according to claim 4 wherein said substep of observing selected features of
pulsatile activity includes the substep of applying gating circuitry to the time variation
of the summed output signal associated with the selected portion of the selected tissue
45 slice.

- 50 8. A method according to claim 4 wherein said substep of observing selected features of
pulsatile activity includes the substeps of:

performing spectral analysis of the summed output signal associated with the selected portion of the selected tissue slice to produce a frequency spectrum associated therewith;

selecting a reference pulsatile signal associated with the heart rate of the subject;

performing spectral analysis of the reference pulsatile signal associated with the heart rate of the subject to produce a frequency spectrum associated therewith; and

comparing the frequency spectrum of the summed output signal associated with the selected portion of the selected tissue slice with the frequency spectrum of the reference pulsatile signal associated with the heart rate of the subject.

9. A method according to claim 8 wherein the reference pulsatile signal associated with the heart rate of the subject is an electrocardiogram signal.
10. A method according to claim 1 wherein said step of activating and focusing includes the substep of varying the selected frequency waveband of the ultrasound waves emitted and received by the ultrasound probes.
11. A method according to claim 1 wherein the frequency waveband of the ultrasound waves emitted and received by the ultrasound probes is selected so as not to be substantially attenuated by bone tissue.
12. A method according to claim 1 wherein the frequency waveband of the ultrasound waves emitted and received by the ultrasound probes has a bandwidth of substantially 0.4 MHz in the frequency range 0.4-30.0 MHz and wherein the output intensity is in the range 100-300 mW/cm².

- 5
13. A method according to claim 1 wherein the selected portion of the selected slice of tissue has a volume in the range 0.1 to 1.0 mm³.
- 10
14. A method according to any of claims 1-13, and substantially as shown and described in conjunction with any of Figures 1A-6.
- 15
15. A method according to any of claims 1-13, and substantially as shown in any of Figures 1A-6.
- 20
- 25
- 30
- 35
- 40
- 45
- 50

1/5




Fig. 1A




Fig. 1B

2/5




Fig. 3




Fig. 2

3/5




Fig. 4





Fig. 5

Fig. 6



THIS PAGE BLANK (USPTO)